

SPECIFICATIONS

GENERAL

RADIO REMOTE	Wireless Transmitter System/w Tethered Backup Remote
VIBRATOR	Standard
WATER TANK	1000L (264 Gal)
WATER PUMP	Hydraulic Power 20 bar (290 psi)
WEAR PARTS	Carbide
OUTRIGGER	Hydraulic Front & Rear
TOOL BOX	Standard
WEIGHT	31,660 lbs/14,360 kg (Model As Shown)

PUMP

OUTPUT:	Rod Side	115 m ³ /h (150 yd ³ /h)
	Piston Side	72 m ³ /h (94 yd ³ /h)
PRESSURE:	Rod Side	92 bar (1334 psi) [‡]
	Piston Side	148 bar (2146 psi) [‡]
STROKES PER MINUTE	Rod Side	30
	Piston Side	19
HARD CHROMED CONCRETE CYLINDER		200 mm x 1400 mm (8" X 83")
S-TUBE SIZE		200 mm x 178 mm (8" x 7")
OUTLET		152 mm (6" ZX)
MAX. AGGREGATE SIZE		63 mm (2.5")
HYDRAULIC PUMP		Rexroth Hydromatic A11VL0260
HYDRAULIC SYSTEM PRESSURE		350 bar (5076 psi)
SWITCHING SYSTEM		Hydraulic w/Manual Override
LUBE SYSTEM (HOPPER)		Lincoln Automatic Greaser
HOPPER CAPACITY		Reinforced Hopper 600 L (159 Gal)

[‡]Not to be used through boom pipe

Contact your sales rep for your chassis options.

Alliance Concrete Pumps Inc. reserves the right to make changes to all specifications