

SPECIFICATIONS

Pump Kit on S 28 X

2023-5 130/80 MSP

U.S. Rod/Piston Metric Rod/Piston

Theor. Concrete Output Per Hour (cubic yards - cubic meters)	208/131	161/100
Maximum Pressure on Concrete (psi - bar)	1007/70	65/95
Maximum Strokes Per Minute	32/32	
Material Cylinder Diameter (in. - mm)	9	230
Material Cylinder Stroke Length (in. - mm)	79	2000
Differential Cylinder Size (in. - mm)	5.1	130
Maximum Aggregate Size (in. - mm)	2.5	63.5

Boom Specifications

	U.S.	Metric
Pipeline Diameter (in. - mm)	5	125
Vertical Reach (ft.-in. - m)	90-11	28
Horizontal Reach (ft.-in. - m)	77-9	23.7
Net Horizontal Reach (ft.-in. - m)	70-5	21.5
Unfolding Height (ft.-in. - m)	19-2	5.8
Section Lengths		
First Section (ft.-in. - m)	23-3	7
Second Section (ft.-in. - m)	18-1	5.5
Third Section (ft.-in. - m)	18-1	5.5
Fourth Section (ft.-in. - m)	18-1	5.5
Slewing Range (degrees)	370°	370°
End hose length (ft. - m)	12	3.7

Specifications are subject to change without prior notice.

