

JFS-12 HP



GENERAL

RADIO REMOTE	Wireless Transmitter System/w Tethered Backup Remote
VIBRATOR	Standard
WATER TANK	750 L (198 G)
WATER PUMP	Hydraulic Power 20 bar (290 psi)
WEAR PARTS	Carbide
OUTRIGGER	Hydraulic Front & Rear
TOOL BOX	Standard
WEIGHT	31,660 lbs/14,360 kg (Model As Shown)
POPULAR UPGRADES†	<ul style="list-style-type: none"> • Air Chuck • Additional Tool Box • Storage Rack • Under Deck Lighting • Heated Water Tank • Heated Hydraulic Tank

PUMP

OUTPUT:	Rod Side	115 m³/h (150 yd³/h)
	Piston Side	72 m³/h (94 yd³/h)
PRESSURE:	Rod Side	92 Bar (1334 psi) †
	Piston Side	148 bar (2146 psi) †
STROKES PER MINUTE	Rod Side	30
	Piston Side	19
HARD CHROMED CONCRETE CYLINDER	200 mm x 2100 mm (8" X 83")	
S-TUBE SIZE	200 mm x 178 mm (8" x 7")	
OUTLET	152 mm (6" ZX)	
MAX. AGGREGATE SIZE	63 mm 2.5"	
HYDRAULIC PUMP	Rexroth Hydromatic A11VLO260	
HYDRAULIC SYSTEM PRESSURE	350 bar (5076 PSI)	
SWITCHING SYSTEM	Hydraulic w/Manual Override	
LUBE SYSTEM (HOPPER)	Lincoln Automatic Greaser	
HOPPER CAPACITY	21.1 cubic ft (600 L) Harsh Mix Hopper	
OUTRIGGER LOAD	50 KN 11,250 LBS	

†More options available, ask your sales rep for details.
Alliance Concrete Pumps Inc. reserves the right to make changes to all specifications